# LaserPro Spirit LS

Smart Innovative Evolution at Its Best







#### **ENGRAVING:**

wood Bamboo Plasile Glass Crystal

Marble Stone මාබ

#### MARKING:

Alumhum Coated Metal **Stafinless** Brass

CUTTING:

Acryllo ගණින **MDF**Board Raper//Board

### **APPLICATIONS:**

Architectural Models Signages Minfature Models Plaques/Trophies Rubber Stamps Toys

Cut-out Letters // Logos **Building Directories** Display Stands **Brochure Stands** 

**Packaging** Tags Spare Part Labels Bottle Labels Desktop Accessories **Customized Gift Items** Keychains Cellphone Accessories Fashion Accessories Image Engraving

- Spacious 25"x18" (640 mm x 460 mm) working area
- Up to 80 IPS high working speed
- Patented SmartACT<sup>™</sup> motion control technology for higher throughput
- Closed-loop DC servo motor for precised movement of laser carriage
- Reliable DuraGuide motion system with reinforced Kevlar belt delivers superb output quality
- Pass-through front and rear doors to accommodate long working pieces
- Plug and play standard USB port for rapid data transmission
- Patented SmartGUARD™ fire alarm device to provide maximum operation safety

- One year warranty for parts and services.
- ( limited warranty on lens, mirror, honeycomb table and consumables.)

  2. Free initial set-up, installation and training on machine operations
- and maintenance Prices subject to 12% EVAT.
- Pictures and specs may slightly vary from actual unit.
   Pictures, features, specs and prices subject to change without prior notice.



MEMBER



Tel: +63 (2) 973-7042 +63 (2) 771-1959 +63 (2) 772-1378

www.graficad-inc.com sales@graficad-inc.com

+63 (2) 772-1379

Specification		Spirit LS
Work Area		25 x 18 in. (640 x 460 mm) Extendable to 29 x 18 in. (740 x 460 mm)
Max. Part Size (W x L x H)	All doors closed	31.5 x 22.4 x 6.5 in. (800 x 570 x 165 mm)
	All doors open	26.8 x ∞ x 6.5 in. (680 x ∞ x 165 mm)
Table Size		31.1 x 20.9 in. (790 x 530 mm)
Dimensions		44.3 x 28.3 x 39.6 in. (1125 x 720 x 1005 mm)
Laser Source		12 to 80W 10.6-µm sealed CO2 Laser / 20W & 60W 9.3-µm sealed CO2 Laser
Cooling		Air-cooled, Operating environment temperature 15°- 30°C (60°- 86°F)
Drive		Closed-loop DC servo control
Maximum Motor Speed		80 IPS**
Throughput*		260.9 in <sup>2</sup> / hr (1683 cm <sup>2</sup> / hr)
Throughput* with SmartACT™ Enabled		322.1 in <sup>2</sup> / hr (2078 cm <sup>2</sup> / hr)
Speed Control		Adjustable from 0.1-100% (Up to 16 color-linked speed settings per job)
Power Control		Adjustable from 0-100% (Up to 16 color-linked power settings per job)
Distance Accuracy		0.254 mm or 0.1% of move, whichever is greater
Z-Axis Movement		Automatic
Focus Lens		Standard 2.0", optional 1.5", 2.5", & 4.0" available
Resolution (DPI)		Available 125, 250, 300, 380, 500, 600, 760, 1000, 1500, 3000
Computer Interface		Standard printer port and USB 2.0** port
Compatible Operating Systems		MS Windows
Memory Buffer		32 MB standard
Display Panel		4-line LCD display showing current file name, total working time, laser power, engraving speed, file(s loaded into memory buffer, setup and diagnostic menus
Safety		Class 3R for red pointer
Operation Voltage		100~240 Volt AC Auto Switching for 30 Watt and below; 200~240 Volt AC Auto Switching for 40 Watt and above models
Power Consumption		700W - 4400W
Air Exhaust System		External exhaust system is required, one 4" connection on the back of the machine

Spirit LS 12WATTS

25WATTS 30WATTS 40WATTS 60WATTS 80WATTS 100WATTS

## **Optional Items**

Item # 101-10P-005 101-25P-001

101-10P-002

Rotary Attachment Honeycomb Air Compressor

















Air Extraction System















www.graficad-inc.com sales@graficad-inc.com +63 (2) 771-1959 +63 (2) 772-1378

Tel: +63 (2) 973-7042